

Model information for hobs

| Miele | | | | | | | |
|--|--|-----------|-------------------|--|---|---|---|
| Model name/ model ID number | | KM 2032 G | | | | | |
| Configuration | | | | | | | |
| Type of hob | Combination | | | | | | - |
| | Self-contained | | | | | | • |
| Support material | Stainless steel | | | | | | • |
| | Ceramic | | | | | | - |
| Operation | HiLight | | | | | | - |
| | Induction | | | | | | - |
| | Gas | | | | | | • |
| Operation | Sensor touchpads +/- | | | | | | - |
| | Switch knob | | | | | | • |
| Dimensions | | | | | | | |
| Product dimensions | Width | cm | 75,0 | | | | |
| | Depth | cm | 52,0 | | | | |
| Cutout dimensions for building in | Width | cm | 56,0 | | | | |
| | Depth | cm | 48,0 | | | | |
| Built-in height | | cm | 3,5 | | | | |
| Building-in height with connection box | | cm | | | | | |
| Rings | | | | | | | |
| Diameter or burner type | 1. Ring | mm | High-speed burner | | | | |
| | 2. Ring | mm | Economy burner | | | | |
| | 3. Ring | mm | Single wok burner | | | | |
| | 4. Ring | mm | Standard burner | | | | |
| | 5. Ring | mm | Standard burner | | | | |
| | 6. Ring | mm | | | | | |
| Ring power levels | 1. Ring | W | 2.600 | | | | |
| | mit Booster | W | - / - | | | | |
| | 2. Ring | W | 1.000 | | | | |
| | mit Booster | W | - / - | | | | |
| | 3. Ring | W | 3.800 | | | | |
| | mit Booster | W | - / - | | | | |
| | 4. Ring | W | 1.750 | | | | |
| | mit Booster | W | - / - | | | | |
| | 5. Ring | W | 1.750 | | | | |
| | mit Booster | W | - / - | | | | |
| | 6. Ring | W | | | | | |
| | mit Booster | W | - / - | | | | |
| Keep-warm area | | | | | | | |
| Net weight | | kg | 15,7 | | | | |
| Electrical specifications | | | | | | | |
| Voltage | | V | 230-240 | | | | |
| Wattage | | W | 25 | | | | |
| Fuse | | A | 1x10 | | x | x | x |
| Connection cable length ²⁾ | | cm | 202 | | | | |
| Interference suppressed | | | • | | | | |
| Mains interference free | | | • | | | | |
| Name and address of supplier | Miele & Cie. KG, Postfach, 33325 Gütersloh | | | | | | |
| Note: | | | | | | | |
| <ul style="list-style-type: none"> • Yes, available <p>¹⁾ Tolerance range +/- 5 cm.</p> <p>²⁾ The length is as follows: The length of the cable between the hob and connection box is 150 cm. Length from connection box is 140 cm.</p> | | | | | | | |
| Note: Table established 07/05. Subject to further development. | | | | | | | |